

# INDUSTRIAL LUBRICANT *Solutions*



- Red in color for easy application
- Performs well under high loads
- Sprays on as liquid then sets as a gel



CARE FOR WORK ENVIRONMENTS®



#### **PENETRATES**

GRS sprays deeply into machinery and equipment, lubricating and protecting even hard-to-reach areas.

#### **LUBRICATES**

The Bentone formulation of this grease enables it to perform under high loads without thinning out, thereby maintaining its excellent lubricating properties. GRS has superior mechanical stability and mobility at low temperatures. Resists caking and hardening as a result of constant load or idle periods.

#### **PROTECTS**

The molecular structure of GRS is designed to resist oxidation even during periods of no load. GRS prevents corrosion from acids, alkalies and salt. GRS is impervious to moisture, will not wash out or weather away. GRS can be sprayed on any metal surface to lubricate and protect.

#### **ECONOMICAL**

GRS is a multipurpose lubrication system in an aerosol can. No need for expensive grease guns or grease application equipment. The multipurpose formulation of GRS will, in many cases, eliminate the need for most special use lubricants.

#### **DIRECTIONS FOR USE:**

Shake well. Spray directly on surface. Allow to "dry" for approximately 15 to 20 minutes. For hard-to-reach areas, use the plastic extension tube.

Please review label and SDS for all product directions, precautions and first aid information.

#### **USES:**

Worm Gears, Casters, Chains, Press Fittings, Hinges, Injection Nozzles, Pumps and Compressors, Motors, Die Bolts, Rack and Pinion, Rollers, Shafts, Sprockets and Bearings (plain, thrust slide, roller).

#### **Application**

Adjuster Screws, Anchor Pins, Couplers, Cam Bushings, Chain Swivel, Clevises, Cable Connections, Gear Housing, Flanges, Deck, Latch Hinges, Valves, Levers, Pump Sub-assemblies, Rollers, Shafts, Propeller Shaft Spline, "U" Joint Bearing, Water Pump Cartridge Insert, Adjustment Screws, Ball Bearings, Brake Cables, Brake Linkages, Chain Links, Clutches, Power Screws, Shackle Pins, Sprockets, Crane-Swivel Connections, Transmission Arms and Pitch Adjuster on Plows

#### **TECHNICAL DATA:**

**APPEARANCE:** opaque red aerosol

**TEMPERATURE RANGE:** 0°F - 350°F

**SPECIFIC GRAVITY:** 0.85

#### **PACKAGING**

121770-12	14 OZ Aerosol/CS12
121770-24	14 OZ Aerosol/CS24



**State Industrial Products**  
5915 Landerbrook Drive  
Mayfield Heights, OH 44124  
To Order Call: 1-866-747-2229  
www.stateindustrial.com

**Canada**  
6935 Davand Drive  
Mississauga, Ontario L5T 1L5  
To Order Call: 1-800-668-6513

**Puerto Rico**  
Royal Industrial Park, Bldg "M"  
Local #5, Carr 869, km 1.5 Palmas  
Cataño, P.R. 00962  
To Order Call: 787-275-3185

