

# INDUSTRIAL LUBRICANTS

## *Solutions*



# OGGL<sup>®</sup>

**OPEN GEAR & WIRE ROPE LUBRICANT**

- Powerful adhesive agents cause it to spread and cling to contact areas
- Creates a uniform coverage
- Withstands extreme pressure, eliminating friction and reducing wear



**State<sup>®</sup>**  
Since 1911

CARE FOR WORK ENVIRONMENTS<sup>®</sup>



## OPEN GEAR & WIRE ROPE LUBRICANT

### WON'T SQUEEZE OUT

Powerful adhesive agents cause OGL to spread and cling to contact areas, assuring uniform coverage. OGL stands up to high loads over extended service periods, withstands extreme pressure, eliminates friction and reduces wear.

### DURABLE PROTECTIVE COATING

OGl is weather resistant, so it minimizes dirt pick-up and protects metal from water and rust. OGL stays flexible and flowing at low temperatures.

### CONVENIENT

OGl sprays on thin and penetrates into hard-to-reach areas. Then OGL thickens into a heavy load-bearing consistency. No heating required. No chipping, flaking or throw off when properly applied, allowing for a neat and economical touch-up lubrication.

### WORKS EVERYWHERE:

Mines  
Cement mills  
Sawmills  
Coke ovens  
Foundries  
Heat treating plants  
Machine shops  
Construction firms  
Dredging firms  
Shipping firms  
Trucking firms  
Docks and ports  
Printers

### USE ON:

Gears  
Winches, cable  
Pennants  
Draglines  
Elevators  
Furnaces  
Lift trucks racks  
Chains, slides  
Forging machines  
Cams  
Leaf springs  
Stamping machines  
Presses and shears

### DIRECTIONS FOR USE:

Shake can well for approximately three minutes before using. Spray 12 to 14 inches from application point.

**IMPORTANT:** Allow ample time (1/2 hour to 1 hour) for lubricant to set up.

Please review label and SDS for all product directions, precautions and first aid information.

### TECHNICAL DATA:

**APPEARANCE:** aerosol spray. Dries to leave a black oil

**SPECIFIC GRAVITY:** 0.85

**AEROSOL FLAME EXTENSION:** >60cm

**WATER WASHOUT OF LUBRICANT:** less than 1% at 100°F

**EXTREME PRESSURE ADDITIVE:** present

**CHLORINATED SOLVENTS:** none present

**STABILITY:** two years

### PACKAGING

121810-12 14 Oz Aerosol/CS12  
121810-24 14 Oz Aerosol/CS24



**State Industrial Products**  
5915 Landerbrook Drive  
Mayfield Heights, OH 44124  
To Order Call: 1-866-747-2229  
www.stateindustrial.com

**Canada**  
6935 Davand Drive  
Mississauga, Ontario L5T 1L5  
To Order Call: 1-800-668-6513

**Puerto Rico**  
Royal Industrial Park, Bldg "M"  
Local #5, Carr 869, km 1.5 Palmas  
Cataño, P.R. 00962  
To Order Call: 787-275-3185

