

FLOOR CARE *Solutions*



Floor Wizard™ **Thick Strip**



- Removes years of extreme floor finish buildup
- Clings to floors and other hard-to-strip surfaces such as stairs, ramps and baseboards
- Works on contact and stays active for up to one hour



CARE FOR WORK ENVIRONMENTS®

Floor Wizard™ Thick Strip

HIGH-PERFORMANCE

Thick Strip is designed to penetrate multiple layers of finish and extreme build-up, allowing for easy removal. Its exclusive formula contains a blend of solvents that break the chemical bond holding the sealer and finish to the floor making removal quick and easy.

TIME-RELEASE FORMULA

Thick Strip's time-release formula begins to work on contact and remains active for up to one hour. Its thickened formula allows it to cling to a variety of surfaces such as baseboards, stairs, ramps and uneven floors.

Note: Not for use on asphalt tiles.

DIRECTIONS FOR USE

EXTREME BUILDUP

1. Stir or mix well before use.
2. Dust mop or sweep floor thoroughly.
3. Apply Thick Strip to work area (800-1000 sq. ft).
4. Using mop or broom, spread solution evenly.
5. Let stand for at least 30 minutes.
6. As the solution begins to absorb the finish, it will become tacky. Apply one gallon of hot water with a mop.
7. Repeat step six until 90% of the finish is absorbed and the solution is thin.
8. Scrub with a black pad and a low speed machine (175-350 rpm), or an automatic scrubber.
9. Pick up the solution with a wet vacuum.
10. If necessary, reapply Thick Strip to remove any remaining finish or sealer.
11. Rinse until all residues are removed.

BASEBOARDS, STAIRS AND RAMPS

1. Apply Thick Strip with a brush or mop
2. Let stand for 10-15 minutes
3. Scrub with stripping pad and a low speed machine or "Doodle Bug" utility pad.
4. Rinse thoroughly

NOTE:

May attack some painted surfaces. Test in a small, inconspicuous area before use.

Please review label and SDS on stateindustrial.com for all product directions, precautions and first aid information.

TECHNICAL DATA

APPEARANCE: thickened gray liquid

ODOR: fresh and clean

pH: 11.2-12.2

FLASHPOINT: none at 200°F

STABILITY: two years

PACKAGING

101866

5 GL Pail



State Industrial Products

5915 Landerbrook Drive
Mayfield Heights, OH 44124
To Order Call: 1-866-747-2229
www.stateindustrial.com

Canada

6935 Davand Drive
Mississauga, Ontario L5T 1L5
To Order Call: 1-800-668-6513

Puerto Rico

Royal Industrial Park, Bldg "M"
Local #5, Carr 869, km 1.5 Palmas
Cataño, P.R. 00962
To Order Call: 787-275-3185

