

INDUSTRIAL LUBRICANTS *Solutions*



- Protects equipment from excessive wear and tear
- Odorless, colorless, non-staining and waterproof
- Prevents rust and corrosion while repelling water and ice

State[®]
Since 1911

CARE FOR WORK ENVIRONMENTS[®]



MULTI-PURPOSE FORMULA

LUB is a silicone lubricant that eliminates and prevents rust, frozen door and trunk locks as well as sticky and squeaky door hinges. Its versatile penetrating formula is long-lasting, non-staining and colorless, making it an ideal add-on to all maintenance shops.

LUB can be used on automobiles to eliminate metal-to-metal noises and rubber-to-metal squeaks. It can be applied to wood, most plastics, metal and leather.

LUB LUBRICATES

LUB utilizes its release agent properties to create a slick, non-sticking silicone surface that speeds up production runs, reduces clean-up times and prevents the build-up of dirt, grime, greases, etc.

MAXIMUM PROTECTION

LUB provides superior lubrication with excellent release agent properties. It leaves a smooth lubricated finish that repels water and ice, preventing rust and corrosion.

LUB IS SAFE

LUB is rated non-toxic for contact with fresh, frozen, cooked or baked food products when used within FDA limits (no more than 10 ppm residual silicone can be imparted to food). It is NSF approved as an H1 lubricant, which means it is approved for general incidental contact.

DIRECTIONS FOR USE:

Shake well and remove protective cap. In an upright position, hold can 8-10 inches from surface to be treated. Point nozzle opening towards surface and press button to apply product thoroughly on surface. Reapply as needed.

*Please review the label and SDS for all product directions, precautions and first aid information.

TECHNICAL INFORMATION:

APPEARANCE: water, white liquid

ODOR: mild solvent

FLAMMABILITY: Aerosol spray is flammable. Silicone lubricant left after drying is nonflammable.

TEMPERATURE RANGE: -35° to 300°F

TOXICITY: Can be used safely around fresh, frozen, cooked or baked food products.

STABILITY: minimum one year

*Does not contain chlorofluorocarbon propellants or 1, 1, 1-trichloroethane.

*NSF certified as a H1 lubricant.

PACKAGING

127666-12 11.5 OZ Aerosol/CS12

127666-24 11.5 OZ Aerosol/CS24



State Industrial Products
5915 Landerbrook Drive
Mayfield Heights, OH 44124
To Order Call: 1-866-747-2229
www.stateindustrial.com

Canada
6935 Davand Drive
Mississauga, Ontario L5T 1L5
To Order Call: 1-800-668-6513

Puerto Rico
Royal Industrial Park, Bldg "M"
Local #5, Carr 869, km 1.5 Palmas
Cataño, P.R. 00962
To Order Call: 787-275-3185

